

The logo for Krube, featuring the word "krube" in a bold, lowercase, sans-serif font. The letter "k" is black with a small orange dot above it. The letter "e" is black with a small blue dot above it. The logo is enclosed in a white circle with a blue border.

krube

SPECIFICATION

MODEL

K-AC120-G230-24

Alternating current tilting vortex blower

SPECIFICATION

Model No. : K-AC120-G230-24

Dimension : 100*68 mm

Bearing System : BALL BEARING

Rated Voltage : 230 VAC

Operating Voltage : 220 ~240 VAC

Rated Current : 0.35A/0.40A

Input Power : 80W/90W

Rated Speed : 2460RPM/2680RPM

Air Flow : 260/280 m³/H±10%

Static Air Pressure : 350/320Pat

Noise Level : 60 dBA±10%

Capacitor : 2uf/500V

Life Expectance : 50000 Hours at Room Temperature

Operation Temperature : -20°C to +80°C

Net Weight : 2.0kg

Protection grade : IP44

Packing : 8 Pcs Per Export Carton

MATERIAL

1.Impeller : Iron leaves	2.The rotor : Aluminum Die-casting
3.Lead Wire : Silicon rubber high temperature line	4.Chassis : Iron leaves

DIMENSIONS: MM

