

80mm-Series Fan



- Material--Frame:Plastics (Flammability:UL94V-0)
Impeller:Plastics (Flammability:UL94V-0)
- Lead Wire-- +Red -Black
Optional Function:Brown(Sensor) Yellow(Control)
- Life Time-- 25000 Hours Sleeve bearing
50000 Hours Ball bearing
- Storage Temperature-- -30°C~+70°C (Non-condensing)
- Bearing Type-- Ball Bearings~Sleeve
- Speed Range-- $\pm 10\%$

Model No.	Rated Voltage	Operating Voltage	Rated Current	Rated Input	Rated Input	Maximum Air Flow		Max.Static Pressure		Noise
	VDC	VDC	AMP	Watt	R.P.M	M ³ /min	CFM	Pa	In H2O	dB-A
K-DC8032-A12-26H	12	7.2~13.2	0.08	0.96	2600	0.66	23.3	26	0.1	21
K-DC8032-A12-40H			0.13	1.56	4000	1.01	35.7	61.2	0.25	33
K-DC8032-A12-60H			0.31	3.72	6000	1.51	53.4	137.7	0.55	44
K-DC8032-A12-67H			0.35	4.2	6700	1.69	59.6	171	0.68	47
K-DC8032-A12-87H			0.59	7.08	8700	2.2	77.7	294	1.18	54
K-DC8032-A12-97H			0.83	9.96	9700	2.45	86.5	360	1.45	57
K-DC8032-A24-26H	24	14.5~27	0.04	0.96	2600	0.66	23.3	26	0.1	21
K-DC8032-A24-40H			0.065	1.56	4000	1.01	35.7	61.2	0.25	33
K-DC8032-A24-60H			0.155	3.72	6000	1.51	53.4	137.7	0.55	44
K-DC8032-A24-67H			0.175	4.2	6700	1.69	59.6	171	0.68	47
K-DC8032-A24-87H			0.295	7.08	8700	2.2	77.7	294	1.18	54
K-DC8032-A24-97H			0.415	9.96	9700	2.45	86.5	360	1.45	57
K-DC8032-A48-26H	48	32~55	0.02	0.96	2600	0.66	23.3	26	0.1	21
K-DC8032-A48-40H			0.035	1.68	4000	1.01	35.7	61.2	0.25	33
K-DC8032-A48-60H			0.08	3.84	6000	1.51	53.4	137.7	0.55	44
K-DC8032-A48-67H			0.09	4.32	6700	1.69	59.6	171	0.68	47
K-DC8032-A48-87H			0.15	7.2	8700	2.2	77.7	294	1.18	54
K-DC8032-A48-97H			0.21	10.08	9700	2.45	86.5	360	1.45	57

80mm-Series Fan

