

80mm-Series Fan



- Material--Frame:Plastics (Flammability:UL94V-0)
Impeller:Plastics (Flammability:UL94V-0)
- Lead Wire-- +Red -Black
Optional Function:Brown(Sensor) Yellow(Control)
- Life Time-- 25000 Hours Sleeve bearing
50000 Hours Ball bearing
- Storage Temperature-- -30°C~+70°C (Non-condensing)
- Bearing Type-- Ball Bearings~Sleeve
- Speed Range-- $\pm 10\%$

Model No.	Rated Voltage	Operating Voltage	Rated Current	Rated Input	Speed	Maximum Air Flow		Max.Static Pressure		Noise
	VDC	VDC	AMP	Watt	R.P.M	M3/min	CFM	Pa	IN H2O	dB-A
K-DC8025-A12-15H	12	7.5~13.2	0.06	0.72	1500	0.42	14.8	7.2	0.02	17
K-DC8025-A12-21H			0.08	0.96	2100	0.58	20.4	14.3	0.05	19
K-DC8025-A12-28H			0.12	1.44	2800	0.78	27.5	25.4	0.1	23
K-DC8025-A12-35H			0.18	2.16	3500	1.01	35.5	40.5	0.16	28
K-DC8025-A12-52H			0.22	2.64	5200	1.46	51.5	87.7	0.35	38
K-DC8025-A12-68H			0.48	5.76	6800	1.91	67.4	150	0.6	45
K-DC8025-A12-74H			0.6	7.2	7400	2.07	73	177.6	0.7	48
K-DC8025-A24-15H	24	14.5~27.5	0.02	0.48	1500	0.42	14.8	7.2	0.02	17
K-DC8025-A24-21H			0.04	0.96	2100	0.58	20.4	14.3	0.05	19
K-DC8025-A24-28H			0.6	1.44	2800	0.78	27.5	25.4	0.1	23
K-DC8025-A24-35H			0.09	2.16	3500	1.01	35.5	40.5	0.16	28
K-DC8025-A24-52H			0.1	2.4	5200	1.46	51.5	87.7	0.35	38
K-DC8025-A24-68H			0.21	5.046	6800	1.91	67.4	150	0.6	45
K-DC8025-A24-74H			0.28	6.72	7400	2.07	73	177.6	0.7	48
K-DC8025-A48-52H	48	29.0-55.0	0.005	2.4	5200	1.46	51.5	87.7	0.35	38
K-DC8025-A48-68H			0.11	5.28	6800	1.91	67.4	150	0.6	45
K-DC8025-A48-74H			0.14	6.72	7400	2.07	73	177.6	0.7	48

80mm-Series Fan

