

# 200mm-Series Fan



- Material--Frame:Aluminum,Impeller Impeller:Plastics (Flammability:UL94V-0)
- Lead Wire-- +Red -Black  
Optional Function:Brown(Sensor) Yellow(Control)
- Life Time-- 50000 Hours Ball bearing
- Storage Temperature-- -30°C~+70°C (Non-condensing)
- Bearing Type-- Ball Bearings~Sleeve
- Speed Range-- ±10%

| Model No.         | Rated Voltage | Operating Voltage | Rated Current | Rated Input | Speed | Maximum Air Flow |      | Max.Static Pressure |        | Noise |
|-------------------|---------------|-------------------|---------------|-------------|-------|------------------|------|---------------------|--------|-------|
|                   | VDC           | VDC               | AMP           | Watt        |       | M3/min           | CFM  | Pa                  | IN H2O |       |
| K-DC20053-A12-42H | 12            | 8.5~13.5          | 2.91          | 35          | 4250  | 13.2             | 465  | 370                 | 1.49   | 62    |
| K-DC20053-A12-50H |               |                   | 4.00          | 48          | 5000  | 15.7             | 553  | 659                 | 2.65   | 66    |
| K-DC20053-A12-65H |               |                   | 8.58          | 103         | 6500  | 20.39            | 718  | 998                 | 4.01   | 72    |
| K-DC20053-A12-75H |               |                   | 13.16         | 158         | 7500  | 24.42            | 860  | 1250                | 5.02   | 78    |
| K-DC20053-A24-42H | 24            | 14.5~27.5         | 1.45          | 35          | 4250  | 13.2             | 465  | 370                 | 1.49   | 62    |
| K-DC20053-A24-50H |               |                   | 2.00          | 48          | 5000  | 15.7             | 553  | 659                 | 2.65   | 66    |
| K-DC20053-A24-65H |               |                   | 4.29          | 103         | 6500  | 20.39            | 718  | 998                 | 4.01   | 72    |
| K-DC20053-A24-75H |               |                   | 6.58          | 158         | 7500  | 24.42            | 860  | 1250                | 5.02   | 78    |
| K-DC20053-A24-85H |               |                   | 9.16          | 220         | 8500  | 28.68            | 1010 | 1488                | 5.98   | 82    |
| K-DC20053-A48-42H | 48            | 29.0~55.0         | 0.72          | 35          | 4250  | 13.2             | 465  | 370                 | 1.49   | 62    |
| K-DC20053-A48-50H |               |                   | 1.00          | 48          | 5000  | 15.7             | 553  | 659                 | 2.65   | 66    |
| K-DC20053-A48-65H |               |                   | 2.14          | 103         | 6500  | 20.39            | 718  | 998                 | 4.01   | 72    |
| K-DC20053-A48-75H |               |                   | 3.29          | 158         | 7500  | 24.42            | 860  | 1250                | 5.02   | 78    |
| K-DC20053-A48-85H |               |                   | 4.58          | 220         | 8500  | 28.68            | 1010 | 1488                | 5.98   | 82    |

