

140mm-Series Fan



- Material--Frame:Aluminum,Impeller
Impeller:Plastics (Flammability:UL94V-0)
- Lead Wire-- +Red -Black
Optional Function:Brown(Sensor) Yellow(Control)
- Life Time-- 50000 Hours Ball bearing
- Storage Temperature-- -30°C~+70°C (Non-condensing)
- Bearing Type-- Ball Bearings~Sleeve
- Speed Range-- ±10%

Model No.	Rated Voltage	Operating Voltage	Rated Current	Rated Input	Rated Input	Maximum Air Flow		Max.Static Pressure		Noise
	VDC	VDC	AMP	Watt	R.P.M	M ³ /min	CFM	MmH2O	In H2O	dB-A
K-DC14038-A12-50H	12	7.2~13.8	4	48	5000	9.24	325.2	49.78	1.96	68
K-DC14038-A12-60H			6	72	6000	10.83	381.2	64.77	2.55	74.5
K-DC14038-A12-65H			7	84	6500	11.65	410.1	69.85	2.75	76.5
K-DC14038-A24-50H	24	14.5~27.5	4	48	5000	9.24	325.2	49.78	1.96	68
K-DC14038-A24-60H			6	72	6000	10.83	381.2	64.77	2.55	74.5
K-DC14038-A24-65H			7	84	6500	11.65	410.1	69.85	2.75	76.5
K-DC14038-A48-50H	48	29~55	4	48	5000	9.24	325.2	49.78	1.96	68
K-DC14038-A48-60H			6	72	6000	10.83	381.2	64.77	2.55	74.5
K-DC14038-A48-65H			7	84	6500	11.65	410.1	69.85	2.75	76.5

