

150mm-Series Fan



- Material--Frame:Plastics (Flammability:UL94V-0)
Impeller:Plastics (Flammability:UL94V-0)
- Lead Wire-- +Red -Black
Optional Function:Brown(Sensor) Yellow(Control)
- Life Time-- 50000 Hours Ball bearing
- Storage Temperature-- -30°C~+70°C (Non-comdensing)
- Bearing Type-- Ball Bearings~Sleeve
- Speed Range-- ±10%

Model No.	Rated Voltage	Operating Voltage	Rated Current	Rated Input	Rated Input	Maximum Air Flow		Max.Static Pressure		Noise
	VDC	VDC	AMP	Watt	R.P.M	M³/min	CFM	MmH2O	In H2O	dB-A
K-DC15051-A12-20H	12	8.5~13.5	0.5	6.0	2000	4.2	148	6.88	0.271	41.5
K-DC15051-A12-25H			0.7	8.4	2500	5.1	180	9.65	0.38	47
K-DC15051-A12-30H			1.2	14.4	3050	6.4	226	13.99	0.551	52
K-DC15051-A12-38H			2.3	27.6	3800	8	282	21.34	0.84	60
K-DC15051-A12-41H			2.9	34.8	4100	8.5	300	24.79	0.976	62
K-DC15051-A12-48H			3.4	49.8	4800	9.9	350	31.42	1.237	66
K-DC15051-A12-65H			6.4	76.8	6500	11.6	410	54.86	2.16	71
K-DC15051-A24-20H	24	14.5~27.5	0.25	6.0	2000	4.2	148	6.88	0.271	41.5
K-DC15051-A24-25H			0.35	8.4	2500	5.1	180	9.65	0.38	47
K-DC15051-A24-30H			0.6	14.4	3050	6.4	226	13.99	0.551	52
K-DC15051-A24-38H			1.15	27.6	3800	8	282	21.34	0.84	60
K-DC15051-A24-41H			1.45	34.8	4100	8.5	300	24.79	0.976	62
K-DC15051-A24-48H			1.7	49.8	4800	9.9	350	31.42	1.237	66
K-DC15051-A24-65H			3.2	76.8	6500	11.6	410	54.86	2.16	71
K-DC15051-A48-20H	48	29~55	0.125	6.0	2000	4.2	148	6.88	0.271	41.5
K-DC15051-A48-25H			0.175	8.4	2500	5.1	180	9.65	0.38	47
K-DC15051-A48-30H			0.3	14.4	3050	6.4	226	13.99	0.551	52
K-DC15051-A48-38H			0.575	27.6	3800	8	282	21.34	0.84	60
K-DC15051-A48-41H			0.725	34.8	4100	8.5	300	24.79	0.976	62
K-DC15051-A48-48H			1.04	49.8	4800	9.9	350	31.42	1.237	66
K-DC15051-A48-65H			1.6	76.8	6500	11.6	410	54.86	2.16	71

150mm-Series Fan

